




Directions:

Staticide® topicals can be applied by spraying, wiping, dipping, transfer roller coating, gravure coating, or flexographic printing. For high production applications, mechanically apply solution by using fine-mist sprayers or foam rollers. The product can also be manually sprayed using a trigger sprayer at 8-12" from desired surface.

SDS available at www.aclstaticide.com.



Product# 530:

4-oz bottle; 12 per case (finger-pump sprayer)

Product# 2003:

1-quart bottle; 12 per case (trigger sprayer)

Product# 2001:

1-gallon bottle; 4 per case

Product# 2001-5:

5-gallon pail

Product# 2001-2:

50-gallon drum



General Purpose Staticide®

Static control for non-porous surfaces

General Purpose Staticide® anti-static topical is easy to use and highly effective in controlling electrostatic charges in industrial manufacturing and static-sensitive environments.

As a key component in any static control program, it is non-toxic, non-flammable, and non-staining. This ready-to-use solution formulated specifically for non-porous surfaces is ideal for eliminating static on plastic parts, equipment, and rubber. With a similar viscosity to water, it can be applied in various ways such as spraying, wiping, or dipping.

General Purpose Staticide® can be used for revitalizing anti-static mats that have lost their dissipative properties.

Ideal for the following applications:

- Dust attraction
- Damage potential to sensitive electronic components and subassemblies during manufacture, testing, packaging, shipping, and receiving
- Data errors, paper jams, and other office machine glitches
- Jamming or slipping of paper, plastics, and other materials during printing, packaging, and converting
- Ignition of combustible vapors, dust, and solvents, causing fire or explosion
- Irregularities caused by static in quality printing, heat sealing, silk screening, lamination, and other special applications
- Static discharge on workbenches and production surfaces

FEATURES

- ❖ Formulated for non-porous surfaces
- ❖ Exceeds MIL-B-81705 and NFPA-56A electrostatic decay criteria
- ❖ Meets requirements for topical anti-stats as listed in the Military Handbook DOD-HDBK-263
- ❖ Proven effective in relative humidity below 15%
- ❖ Decays static in less than 2 seconds
- ❖ Surface resistance between 10^9 - 10^{10} ohms
- ❖ One gallon covers approximately 2000 sq.ft. per gallon
- ❖ Lasts from weeks to months depending on application