



Staticide® 4018 Acrylic Dissipative Floor Finish

Low Cost Protection against ESD

Staticide® 4018 Acrylic Dissipative Floor Finish offers static protection at a reasonable price. This economical formula leaves a durable, glossy finish that can last up to six months with proper maintenance. This floor finish is a popular choice for companies with industrial areas that require frequent cleaning.

Easy to apply and maintain, Staticide® 4018 Acrylic Dissipative Floor Finish leaves floors with a surface resistance of 10^8 - 10^9 ohms, complying with ANSI/ESD S20.20 guidelines. This water-based formula is RoHS and REACH compliant, biodegradable, non-flammable, and free of acids, alkalis, ammonia, formaldehyde and phthalates.

Directions:

Clean floor and apply two to three thin coats of floor finish with a dedicated lint-free mop. Wait a minimum of one hour between coats. See application instructions for details.

Maintenance:

Sweep or dust mop daily. Do not use sweeping compound. Periodically clean with a 1:1 dilution of water and floor finish. Apply a thin top coat of floor finish every 4 – 6 weeks. For heavy cleaning, use Staticide® 4100 Restorer Cleaner. Consult maintenance procedures for details and precise instructions.

Ideal for the following applications:

- Production areas
- Warehousing
- Shipping areas
- Electronics repair facilities

FEATURES

- ❖ Covers approximately 1500 – 2000 sq. ft. per gallon
- ❖ V.O.C. < 4%
- ❖ 18% Solids, ±5%
- ❖ UL listed for slip resistance
- ❖ Compliant to ANSI/ESD S20.20
- ❖ Surface resistance (RTT): $10e8$ – $10e9$ ohms @ 100v at 12 RH
- ❖ Strip cycle is 6 months
- ❖ Use on vinyl, linoleum, or ceramic tile

Product# 4018-1: 1-gallon container; 4 per case

Product# 4018-5: 5-gallon pail

Product# 4018-2: 54-gallon drum