

Staticide® Universal Cleaner Concentrate

Powerful degreaser for ESD paint

Staticide Universal Cleaner Concentrate is the go-to industrial cleaning and surface preparation solution. This versatile cleaner excels in tackling dirt and grease while being gentle on sensitive surfaces like ESD tile, epoxy, and paint. It safeguards surfaces from damage and corrosion with a non-abrasive formulation and a neutral pH balance.

This essential cleaner is ideal for preparing concrete surfaces for paint application to ensure adhesion and for cleaning and maintaining 4400 Staticide ESD Polycoat Paint.



Directions:



To prepare floor for painting: Sweep floor to remove dirt and debris. Dilute Staticide Universal Cleaner 5:1 (5 parts water to 1 part concentrate). Scrub with auto scrubber with stripping pad or a stiff bristle broom brush. Rinse twice with water before applying paint.

To maintain paint: Allow floor to dry 3 days (72 hours minimum) at not less than 60°F before cleaning.

Dilute Staticide Universal Cleaner 5:1 (5 parts water to 1 part concentrate) and clean with a lint-free mop. For auto scrubbers, gently scrub diluted solution with clean polishing pad. Use 1500 - 2000 RPM with a light pressure setting.

SDS available at www.aclstaticide.com.

Product# 4040-1: 1-gallon bottle; 4 per case

Product# 4040-5: 5-gallon pail

Product# 4040-2: 50-gallon drum

Ideal for the following applications:

- Electronic manufacturing facilities
- Maintaining ESD paint
- Preparing concrete floors for paint application

FEATURES

- ❁ **Powerful degreaser**
- ❁ **Safe for ESD tile, epoxy, and paint**
- ❁ **Neutral pH**
- ❁ **No phosphate, ammonia, or bleach**
- ❁ **Dilution ratio 5:1 (5 parts water to 1 part cleaner)**
- ❁ **Covers approximately 5000 square feet per diluted gallon**

